

Product Information Sheet

DW32 & DW42

The Kingray[®] DW32 and DW42 are high gain professional MATV distribution amplifiers. They feature separate VHF & UHF antennas inputs or a combination antenna input. Featuring 'F' connector inputs, adjustable gain control and a two stage cable equalization circuit, These amplifiers include a three band adjustable equalization circuit ensuring that all thee bands (44-144MHz, 174-300MHZ, 470-860MHz) are all output at a similar level. The amplifiers are housed in a die cast enclosure for maximum protection from stray signals. Typically these amplifiers would be used in large multiple outlet systems like hotels, motels and apartment blocks. Both amplifiers also include a –30dB test point.



	FREQUENCY	GAIN	INPUTS	NOISE FIGURE	GAIN CONTROL	OUTPUT	POWER SUPPLY
VHF	44-230	26-28	2	3.5dB	10	112	Packed with (PSK12S)
UHF	470-860	32			10		



	FREQUENCY	GAIN	INPUTS	NOISE FIGURE	GAIN CONTROL	OUTPUT	POWER SUPPLY
VHF	44-144	35-37		3.5dB	20	112	
	176-300		1, 2 or Com-		20		Packed without (Needs PSK18S)
UHF	470-860	40	bined		20		

Other Related Products

"Professional Kingray®

distribution amplifiers "

Email: sales@alvin.com.au

Website: www.alvin.com.au

Products for the 21st Century

All Specifications are subject to change without notice. All care is taken in the compiling of this information sheet, but errors and omissions can occur. Prospective users should not rely solely on this sheet in deciding the suitability of this product.